

Primatech®

FASTENING SYSTEM FOR HARDWOOD FLOOR



NEW

Q550 SOLID/ENGINEERED PNEUMATIC FLOORING NAILER

Primatech Q550 Serie offers the most advanced technology (patent pending) yet delivered by a pneumatic floor fastening tool. Specifically designed for the installation of 3/8" to 5/8" (10 to 16 mm) flooring, jobsite efficiency is ensured with features such as compact design, high speed discharge valve and a new user friendly adjustable base plate which eliminate the use of shims.

INNOVATIVE AIR VALVE

Primatech's exclusive G2 air valve is setting new standards. Still extremely powerful and smooth, it features high speed discharge to minimize air consumption and compact design to install closer to the wall. Also, when it's time to service the user friendly design calls for an easy task.

- Primatch G2 "snap-in" air valve assembly (tool-less wear ring change)
- Primatch G2 "spin-on" head assembly (tool-less access to internal parts)
- Powerful valve, will countersink the fasteners independently of the striking force

INNOVATIVE ADJUSTABLE BASE PLATE

The Q550's fully adjustable base plate is second to none. At first it sets against the front of the tongue which reduces the risk of damaging the top edge. Secondly, it features a shim less height adjustment through the action of a cam knob. Combined together, they allow for infinite adjustment resulting in a perfect positioning of the fastener into the nail pocket of the board.

Features

- Uses Primatch 18 GA fasteners
- Compact design to get closer to end walls
- Large composite base to increase stability and minimize damage to prefinished floors
- Exclusive contact safety device activated when tool is positioned on the flooring
- Ergonomic comfort grip handle
- Quick loading magazine with spring loaded nail pusher
- 2.8 lbs (1.3 kg) non marring mallet included



Applications

3/8" to 5/8" (10 to 16 mm)
solid/engineered
hardwood flooring

Specifications

Weight: 8.75 lbs (3.96 kg)
Height: 17 3/4" (451 mm)
Length: 14 1/2" (368 mm)
Width: 5 1/4" (133 mm)
Capacity: 110 nails
Operating pressure: 85 - 100 psi
Lubrication : few drops daily,
non detergent oil only

FASTENERS

L cleats, 18 GA
1 1/4" 1 1/2" (32 mm, 38 mm)

Primatech®

LABORATOIRE PRIMATECH INC.
1135, rue Jérémie-Fortin
Québec, Qc,
Canada G1J 1R8

Tel.: 1 (418) 522-7744
USA / CAN: 1 (800) 363-1962
Fax: 1 (418) 522-7466
sales@primatech.ca
www.primatech.ca